

PRODUCT SPECIFICATION & TECHNICAL DATASHEET

PW39 - Extra Wrap Around Safety Glasses

Collection: Eye Protection **Range:** Eye Protection **Materials:** Polycarbonate

Inner Pack: 12 Outer Carton: 288

Product information

Expertly designed lightweight spectacles with outstanding optical quality. The one-piece curved lens offers unobstructed vision and the comfortable nose bridge allows for extended use.

Eye Protection

PORTWEST® eye protection range includes spectacles, safety goggles and visors, designed to protect the eyes and face of workers from injuries which may occur during working activities. TECHNICAL SPECTACLES: High performance and cutting edge styles. SPORT SPECTACLES: Light weight and modern design. CLASSIC SPECTACLES: Essential PPE safety eyewear styles.

Eye Protection

PORTWEST eye protection range includes spectacles, safety goggles and visors, designed to protect the eyes and face of the workers from injuries which may occur during working activities. TECHNICAL SPECTACLES: High performance and cutting edge styles. SPORT SPECTACLES: Light weight and modern design. CLASSIC SPECTACLES: Essential PPE safety eyewear styles.

Standards

EN 166 (1 FT) EN 170 (2C-1.2) EN 172 (5-3.1) AS/NZS 1337.1

Features

- · Lightweight wrap-around design
- Single panoramic lens glasses
- Excellent side protection
- Dual material side arms
- Soft nose bridge for a secure and comfortable fit
- Single wrap-around lens for exceptional eye coverage and protection
- \bullet UV protection helps to prevent eye damage from harmful ultraviolet rays
- Anti-scratch coating for added durability
- CE certified
- UKCA marked
- Retail bag which aids presentation for retail sales



PRODUCT SPECIFICATION & TECHNICAL DATASHEET

PW39 - Extra Wrap Around Safety Glasses Commodity Code: 9004901000

Test House

SGS FIMKO Ltd (Notified Body No.: NB: 0598)

Takomotie 8 , Finland

Contact: sgs.fimko@sgs.com Cert No: 0598/PPE/23/3125

Carton Dimensions/Weight

Item	Colour	Len	Wid	Hgt	Weight(Kg)	Cubic(m³)	EAN13	GTIN/DUN14
PW39CLR	Clear	55.0	45.0	50.0	0.0400	0.1238	5036108171989	25036108636185