


PRODUCT SPECIFICATION & TECHNICAL DATASHEET

PW60 - Gas Welding Goggles

Collection: Eye Protection Range: PPE Materials: PVC, Polycarbonate, Elastic Inner Pack: 12 Outer Carton: 144

Product information

When using oxyacetylene for gas cutting or welding, the PW60 offers high performance with a shade factor 5. A soft comfortable frame with flip up lens allows the goggle to be used for grinding operations.



PORTWEST® eye protection range includes spectacles, safety goggles and visors, designed to protect the eyes and face of workers from injuries which may occur during working activities. TECHNICAL SPECTACLES: High performance and cutting edge styles. SPORT SPECTACLES: Light weight and modern design. CLASSIC SPECTACLES: Essential PPE safety eyewear styles.

PPE

Portwest Head PPE range applies the latest standards to deliver the highest level of protection. Comfortable and lightweight, the PPE range will ensure a pleasant wear, even for long periods of use. Your safety is our mission.

Standards

EN 166 (1 F) EN 169 shade 5 EN 175 (F)



Features

- Indirect ventilation
- Flexible PVC frame for ultra comfort
- Stand-off position for intermittent use
- Adjustable elastic headband for a perfect fit
- Ideal for welding and metal handling
- Elasticated straps
- \bullet UV protection helps to prevent eye damage from harmful ultraviolet rays
- Anti-scratch coating for added durability
- CE certified
- UKCA marked
- Retail bag which aids presentation for retail sales



PRODUCT SPECIFICATION & TECHNICAL DATASHEET

PW60 - Gas Welding Goggles Commodity Code: 9004901000

Test House

BSI Group The Netherlands B.V. (Notified Body No.: NB: 2797) John M. Keynesplein 9 , The Netherlands Cert No: CE 808507

BSI Assurance UK Ltd (Notified Body No.: AB: 0086) The British Standards Institution MK5 8PP, United Kingdom Cert No: UKCA 764127

Carton Dimensions/Weight

Item	Colour	Len	Wid	Hgt	Weight(Kg)	Cubic(m ³)	EAN13	GTIN/DUN14
PW60BGR	Bottle Green	58.0	43.0	60.0	0.1540	0.1496	5036108139033	25036108636529