

PRODUCT SPECIFICATION & TECHNICAL DATASHEET

PW68 - Welding Safety Spectacles

Collection: Eye Protection **Range:** Eye Protection **Materials:** Polycarbonate

Inner Pack: 12 Outer Carton: 288

Product information

Multipurpose Shade 5 lens with lateral protection and adjustable arms for customised comfort.

Eye Protection

PORTWEST® eye protection range includes spectacles, safety goggles and visors, designed to protect the eyes and face of workers from injuries which may occur during working activities. TECHNICAL SPECTACLES: High performance and cutting edge styles. SPORT SPECTACLES: Light weight and modern design. CLASSIC SPECTACLES: Essential PPE safety eyewear styles.

Eye Protection

PORTWEST eye protection range includes spectacles, safety goggles and visors, designed to protect the eyes and face of the workers from injuries which may occur during working activities. TECHNICAL SPECTACLES: High performance and cutting edge styles. SPORT SPECTACLES: Light weight and modern design. CLASSIC SPECTACLES: Essential PPE safety eyewear styles.

Standards

EN 166 (1 F) EN 169 shade 5



Features

- · Single panoramic lens glasses
- Extendable side arms for secure and comfortable fit
- Excellent side protection
- Moulded side shield and browguard for optimised protection against impacts
- \bullet Ideal for welding and metal handling
- UV protection helps to prevent eye damage from harmful ultraviolet ravs
- \bullet Anti-scratch coating for added durability
- CE certified
- UKCA marked
- Retail bag which aids presentation for retail sales
- Individually packed for vending machines



PRODUCT SPECIFICATION & TECHNICAL DATASHEET

PW68 - Welding Safety Spectacles Commodity Code: 9004901000

Test House

INSPEC International B.V. (Notified Body No.: NB: 2849)

Beechavenue 54 - 62

, Netherlands

Cert No: PPE19161614

INSPEC International Ltd. (Notified Body No.: AB: 0194)

56 Leslie Hough Way

M6 6AJ, UK

Carton Dimensions/Weight

Item	Colour	Len	Wid	Hgt	Weight(Kg)	Cubic(m³)	EAN13	GTIN/DUN14
PW68BGR	Bottle Green	55.0	45.0	50.0	0.0440	0.1238	5036108259007	25036108748239