

PW90 - All Terrain + HRO

Collection: Eye Protection

Range: Eye Protection

Materials: Polycarbonate, PP, Nylon, ABS, Polyoxymethylene, PVC

Outer Carton: 12

Product information

An ideal solution for face and hearing protection (PW48) where no helmet is required. It protects against particle impact, liquid splashes and dangerous noise. Spare parts available.

Eye Protection

PORTWEST® eye protection range includes spectacles, safety goggles and visors, designed to protect the eyes and face of workers from injuries which may occur during working activities. TECHNICAL SPECTACLES: High performance and cutting edge styles. SPORT SPECTACLES: Light weight and modern design. CLASSIC SPECTACLES: Essential PPE safety eyewear styles.

Eye Protection

PORTWEST® eye protection range includes spectacles, safety goggles and visors, designed to protect the eyes and face of the workers from injuries which may occur during working activities. TECHNICAL SPECTACLES: high performance and cutting edge styles. SPORT SPECTACLES: light weight and modern design. CLASSIC SPECTACLES: essential PPE safety eyewear styles.

Standards

EN 352-1
EN 166 (1 B / 3 B)
EN 352-1 (SNR 27dB)



Features

- Certified
- Retail box which aids presentation for retail sales
- Lightweight and comfortable
- Replacement accessories available
- CE-CAT III
- Replacement visor available
- Wheel ratchet size adjustment for easy fitting
- Browguard-visor combination with headband ear defenders
- Durable Polycarbonate visor with 1mm thickness
- Clear visor for medium-energy impact protection
- Ear defenders clip into headgear securely

PW90 - All Terrain + HRO
Commodity Code: 6506101000

Test House

BSI Group The Netherlands B.V. (Notified Body No.: NB: 2797)
John M. Keynesplein 9
, The Netherlands
Cert No: CE 808507

BSI Assurance UK Ltd (Notified Body No.: AB: 0086)
The British Standards Institution
MK5 8PP, United Kingdom
Cert No: UKCA 764127

Carton Dimensions/Weight

Item	Colour	Len	Wid	Hgt	Weight(Kg)	Cubic(m ³)	EAN13	GTIN/DUN14
PW90YER	Yellow	65.0	30.0	42.0	0.6320	0.0819	5036108149872	25036108636628