

B0676E - Bowling S3L ESD FO SR

Collection: Record

Upper: Water-Resistant Technical Textile and Suede Leather

Lining: SmellStop Antiodor and Antibacterial*

Midsole: Fresh'n Flex

Toecap: SlimCap

Sole: Antifatigue AirTech Single Density

Outer Carton: 10

Record

Record antifatigue footwear collection offers an answer to the demand for lightweight design.

Standards

EN ISO 20345:2022 S3L (ESD FO SR)

CEI EN 61340-5-1

CEI EN 61340-4-3

CEI EN 61340-4-5



Features

- Anti-static footwear
- Water resistant upper to prevent water penetration
- Non-magnetic - nickel and ferrous free
- 200 joules resistant toe-cap
- Puncture resistant sole
- Shock absorption in the heel region
- Hydrocarbons resistant
- Electronic devices protection from electrostatic discharges
- Men's width
- Women's width
- Orthopaedic made to measure footbed, complying with european norms DGUV112-191

B0676E - Bowling S3L ESD FO SR
Commodity Code: 6404199000

Test House

CIMAC (Notified Body No.: 0465)

Via Aguzzafame 60/b

27029, ITALIE

Cert No: N° F-113-02435-19 Rev.1

Carton Dimensions/Weight

| Item | Colour | Len | Wid | Hgt | Weight(Kg) | Cubic(m ³) | EAN13 | GTIN/DUN14 |
|-------------|--------|------|------|------|------------|------------------------|---------------|------------|
| B0676EBKB36 | | 67.0 | 41.0 | 36.0 | 1.0500 | 0.0989 | 8050262500741 | |
| B0676EBKB37 | | 67.0 | 41.0 | 36.0 | 1.1100 | 0.0989 | 8050262500758 | |
| B0676EBKB38 | | 67.0 | 41.0 | 36.0 | 1.1100 | 0.0989 | 8050262500765 | |
| B0676EBKB39 | | 67.0 | 41.0 | 36.0 | 1.1700 | 0.0989 | 8050262500772 | |
| B0676EBKB40 | | 67.0 | 41.0 | 36.0 | 1.2000 | 0.0989 | 8050262500789 | |
| B0676EBKB41 | | 67.0 | 41.0 | 36.0 | 1.2400 | 0.0989 | 8050262500796 | |
| B0676EBKB42 | | 67.0 | 41.0 | 36.0 | 1.2500 | 0.0989 | 8050262500802 | |
| B0676EBKB43 | | 67.0 | 41.0 | 36.0 | 1.3100 | 0.0989 | 8050262500819 | |
| B0676EBKB44 | | 67.0 | 41.0 | 36.0 | 1.3300 | 0.0989 | 8050262500826 | |
| B0676EBKB45 | | 67.0 | 41.0 | 36.0 | 1.3900 | 0.0989 | 8050262500833 | |
| B0676EBKB46 | | 67.0 | 41.0 | 36.0 | 1.4200 | 0.0989 | 8050262500840 | |
| B0676EBKB47 | | 67.0 | 41.0 | 36.0 | 1.4900 | 0.0989 | 8050262500857 | |
| B0676EBKB48 | | 67.0 | 41.0 | 36.0 | 1.5300 | 0.0989 | 8050262500864 | |