

## **B0967A - Sirius Sandal S1PL ESD FO SR**

**Collection:** Smart Evo

**Upper:** TECHNICAL FABRIC

**Insole:** Wire Lace System

**Lining:** SmellStop Antibacterial

**Midsole:** AirTech Single Density

**Toecap:** SlimCap

**Sole:** AirTech Single Density

**Outer Carton:** 10

### **Smart Evo**

The lightweight and flexible range with minimalist style.

### **Standards**

EN ISO 20345:2022 S1PL (FO SR)

**NO  
IMAGE  
AVAILABLE**

### **Features**

- 200 joules resistant toe-cap
- Shock absorption in the heel region
- Anti-static footwear
- Puncture resistant sole
- Hydrocarbons resistant
- SR - Slip Resistance Ceramic and Glycerin
- Suitable for use in ESD environments
- Metal free
- Orthopaedic made to measure footbed, complying with european norms DGUV112-191

**B0967A - Syrius Sandal S1PL ESD FO SR**  
**Commodity Code: 6402990500**

**Test House**

CIMAC (Notified Body No.: 0465)  
Via Aguzzafame 60/b  
27029, ITALIE  
Cert No: N° F-113-06256-23 Rev.1

**Carton Dimensions/Weight**

| Item        | Colour | Len  | Wid  | Hgt  | Weight(Kg) | Cubic(m <sup>3</sup> ) | EAN13         | GTIN/DUN14 |
|-------------|--------|------|------|------|------------|------------------------|---------------|------------|
| B0967ABKG36 |        | 68.0 | 41.0 | 38.0 | 1.0270     | 0.1059                 | 8052530127100 |            |
| B0967ABKG37 |        | 68.0 | 41.0 | 38.0 | 0.9990     | 0.1059                 | 8052530127117 |            |
| B0967ABKG38 |        | 68.0 | 41.0 | 38.0 | 0.9990     | 0.1059                 | 8052530127124 |            |
| B0967ABKG39 |        | 68.0 | 41.0 | 38.0 | 1.1430     | 0.1059                 | 8052530127131 |            |
| B0967ABKG40 |        | 68.0 | 41.0 | 38.0 | 0.9990     | 0.1059                 | 8052530127148 |            |
| B0967ABKG41 |        | 68.0 | 41.0 | 38.0 | 1.2230     | 0.1059                 | 8052530127155 |            |
| B0967ABKG42 |        | 68.0 | 41.0 | 38.0 | 1.2730     | 0.1059                 | 8052530127162 |            |
| B0967ABKG43 |        | 68.0 | 41.0 | 38.0 | 1.3100     | 0.1059                 | 8052530127179 |            |
| B0967ABKG44 |        | 68.0 | 41.0 | 38.0 | 1.3920     | 0.1059                 | 8052530127186 |            |
| B0967ABKG45 |        | 68.0 | 41.0 | 38.0 | 0.9990     | 0.1059                 | 8052530127193 |            |
| B0967ABKG46 |        | 68.0 | 41.0 | 38.0 | 0.9990     | 0.1059                 | 8052530127209 |            |
| B0967ABKG47 |        | 68.0 | 41.0 | 38.0 | 1.5680     | 0.1059                 | 8052530127216 |            |
| B0967ABKG48 |        | 68.0 | 41.0 | 38.0 | 1.5630     | 0.1059                 | 8052530127223 |            |