

## **B1018 - K-Up Shoe O2 ESD FO SRC**

**Collection:** Kaptiv RXT

**Upper:** Water-Resistant Microfibre

**Insole:** Wire Lace System

**Lining:** SmellStop Antibacterial

**Sole:** PU/TPU

**Outer Carton:** 10

### **Kaptiv RXT**

#### **Base**

Comfort is what has inspired Base Protection since its first day of activity. The company produces safety footwear, combining technology and functional requirements, to respond to professional and more demanding clients.



### **Standards**

CEI EN 61340-4-3

CEI EN 61340-4-5

CEI EN 61340-5-1

EN ISO 20347:2012 O2 (ESD SRC)

### **Features**

- Overcap for a higher abrasion resistance
- i-daptive® Technology dissipates high impact energy for a dynamic comfort solution
- Anti-static footwear
- Shock absorption in the heel region
- Hydrocarbons resistant
- Water resistant upper
- Electronic devices protection from electrostatic discharges
- Men's width
- Women's width
- Suitable for use in ESD environments

**B1018 - K-Up Shoe O2 ESD FO SRC**  
**Commodity Code: 6404199000**

**Test House**

A.N.C.I. Servizi S.R.L (CIMAC) (Notified Body No.: NB: 0465)

Via Alberto Riva Villasanta, 3

, Italy

Cert No: F-113-04866-21

**Carton Dimensions/Weight**

Item	Colour	Len	Wid	Hgt	Weight(Kg)	Cubic(m <sup>3</sup> )	EAN13	GTIN/DUN14
B1018BKR36	Black	67.0	41.0	36.0	0.9620	0.0989	8050262508761	
B1018BKR37	Black	67.0	41.0	36.0	0.9940	0.0989	8050262508778	
B1018BKR38	Black	67.0	41.0	36.0	1.0340	0.0989	8050262508785	
B1018BKR39	Black	67.0	41.0	36.0	1.0500	0.0989	8050262508792	
B1018BKR40	Black	67.0	41.0	36.0	1.0820	0.0989	8050262508808	
B1018BKR41	Black	67.0	41.0	36.0	1.1220	0.0989	8050262508815	
B1018BKR42	Black	67.0	41.0	36.0	1.1840	0.0989	8050262508822	
B1018BKR43	Black	67.0	41.0	36.0	1.2140	0.0989	8050262508839	
B1018BKR44	Black	67.0	41.0	36.0	1.2480	0.0989	8050262508846	
B1018BKR45	Black	67.0	41.0	36.0	1.2960	0.0989	8050262508853	
B1018BKR46	Black	67.0	41.0	36.0	1.3520	0.0989	8050262508860	
B1018BKR47	Black	67.0	41.0	36.0	1.3720	0.0989	8050262508877	
B1018BKR48	Black	67.0	41.0	36.0	1.4340	0.0989	8050262508884	