

## **B1041 - K-Hurry Shoe/K-Boogie Shoe S3L HRO FO SR**

**Collection:** Kaptiv

**Upper:** Nubuck

**Insole:** Wire Lace System

**Lining:** SmellStop Antibacterial

**Midsole:** Fresh'n Flex

**Toecap:** Wire Lace System

**Sole:** PU/Rubber

**Inner Pack:** 1

**Outer Carton:** 10

### **Kaptiv**

The first safety footwear range with stability control, designed to offer incredible dynamic comfort.

### **Base**

Comfort is what has inspired Base Protection since its first day of activity. The company produces safety footwear, combining technology and functional requirements, to respond to professional and more demanding clients.

### **Standards**

EN ISO 20345:2022 S3 (HRO FO SR)

EN ISO 20345:2011 S3

**NO  
IMAGE  
AVAILABLE**

### **Features**

- Anti-static footwear
- Shock absorption in the heel region
- 200 joules resistant toe-cap
- Hydrocarbons resistant
- Heat resistant 1 minute up to 300°C
- SR - Slip Resistance Ceramic and Glycerin
- Puncture resistant sole
- Water resistant upper
- Orthopaedic made to measure footbed, complying with european norms DGUV112-191
- Men's Width 12
- Women's Width 10.5

## **B1041 - K-Hurry Shoe/K-Boogie Shoe S3L HRO FO SR** **Commodity Code: 6403400000**

### **Test House**

CIMAC (Notified Body No.: 0465)  
Via Aguzzafame 60/b  
27029, ITALIE  
Cert No: N° F-113-05823-22

### **Carton Dimensions/Weight**

Item	Colour	Len	Wid	Hgt	Weight(Kg)	Cubic(m <sup>3</sup> )	EAN13	GTIN/DUN14
B1041BRO36		68.0	41.0	38.0	1.2020	0.1059	8052530127506	
B1041BRO37		68.0	41.0	38.0	1.2340	0.1059	8052530127513	
B1041BRO38		68.0	41.0	38.0	1.3080	0.1059	8052530127520	
B1041BRO39		68.0	41.0	38.0	1.3200	0.1059	8052530127537	
B1041BRO40		68.0	41.0	38.0	1.3800	0.1059	8052530127544	
B1041BRO41		68.0	41.0	38.0	1.4270	0.1059	8052530127551	
B1041BRO42		68.0	41.0	38.0	1.4940	0.1059	8052530127568	
B1041BRO43		68.0	41.0	38.0	1.5050	0.1059	8052530127575	
B1041BRO44		68.0	41.0	38.0	1.5710	0.1059	8052530127582	
B1041BRO45		68.0	41.0	38.0	1.6270	0.1059	8052530127599	
B1041BRO46		68.0	41.0	38.0	1.6880	0.1059	8052530127605	
B1041BRO47		68.0	41.0	38.0	1.7220	0.1059	8052530127612	
B1041BRO48		68.0	41.0	38.0	1.8130	0.1059	8052530127629	