

B1601 - T-Rex Mid/T-Wall Mid S3S HRO CI HI LG FO SR

Collection: Fortrex

Upper: Water-Resistant Nubuck

Insole: Wire Lace System

Lining: SmellStop Antibacterial

Toecap: SlimCap

Sole: Rubber

Outer Carton: 10

Fortrex

Base

Comfort is what has inspired Base Protection since its first day of activity. The company produces safety footwear, combining technology and functional requirements, to respond to professional and more demanding clients.

Standards

EN ISO 20345:2022 S3S (HRO CI HI LG SC FO SR)

**NO
IMAGE
AVAILABLE**

Features

- 200 joules resistant toe-cap
- Puncture resistant sole
- Anti-static footwear
- Shock absorption in the heel region
- Hydrocarbons resistant
- Water resistant upper
- Heat resistant 1 minute up to 300°C
- Heat insulation up to 150°C
- Cold insulation up to -17°C
- Men's width

B1601 - T-Rex Mid/T-Wall Mid S3S HRO CI HI LG FO SR **Commodity Code: 6403993300**

Test House

CIMAC (Notified Body No.: 0465)
Via Aguzzafame 60/b
27029, ITALIE
Cert No: N° F-113-05707-22 Rev. 1

CIMAC (Notified Body No.: 0465)
Via Aguzzafame 60/b
27029, ITALIE
Cert No: N° F-113-05707-22 Rev. 1

Carton Dimensions/Weight

Item	Colour	Len	Wid	Hgt	Weight(Kg)	Cubic(m ³)	EAN13	GTIN/DUN14
B1601BRO36		68.0	41.0	38.0	1.4190	0.1059	8052530122419	
B1601BRO37		68.0	41.0	38.0	1.5660	0.1059	8052530122426	
B1601BRO38		68.0	41.0	38.0	1.6310	0.1059	8052530122433	
B1601BRO39		68.0	41.0	38.0	1.6680	0.1059	8052530122440	
B1601BRO40		68.0	41.0	38.0	1.7140	0.1059	8052530122457	
B1601BRO41		68.0	55.0	38.0	1.8460	0.1421	8052530122464	
B1601BRO42		68.0	55.0	38.0	1.8540	0.1421	8052530122471	
B1601BRO43		68.0	55.0	38.0	1.8980	0.1421	8052530122488	
B1601BRO44		68.0	55.0	38.0	2.0220	0.1421	8052530122495	
B1601BRO45		68.0	55.0	38.0	2.0660	0.1421	8052530122501	
B1601BRO46		68.0	55.0	38.0	2.2080	0.1421	8052530122518	
B1601BRO47		68.0	55.0	38.0	2.2780	0.1421	8052530122525	
B1601BRO48		68.0	55.0	38.0	2.2070	0.1421	8052530122532	