

## **B1611 - T-Massive S3S HRO CI HI LG FO SR**

**Collection:** Fortrex

**Upper:** Water-Resistant Nubuck

**Insole:** Wire Lace System

**Lining:** SmellStop Antibacterial

**Midsole:** Polyurethane

**Toecap:** SlimCap

**Sole:** Rubber

**Outer Carton:** 10

### **Fortrex**

#### **Base**

Comfort is what has inspired Base Protection since its first day of activity. The company produces safety footwear, combining technology and functional requirements, to respond to professional and more demanding clients.

### **Standards**

EN ISO 20345:2022 S3S (HRO CI HI LG SC FO SR)

**NO  
IMAGE  
AVAILABLE**

### **Features**

- Men's Width 12
- Women's Width 10.5
- 200 joules resistant toe-cap
- Anti-static footwear
- Shock absorption in the heel region
- Water penetration and absorption of the upper
- Puncture Resistant 3mm
- Heat resistant 1 minute up to 300°C
- Cold insulation up to -17°C
- Heat insulation up to 150°C
- Ladder grips

## **B1611 - T-Massive S3S HRO CI HI LG FO SR** **Commodity Code: 6403993300**

### **Test House**

CIMAC (Notified Body No.: 0465)

Via Aguzzafame 60/b

27029, ITALIE

Cert No: N° F-113-05711-22 Rev. 1

### **Carton Dimensions/Weight**

Item	Colour	Len	Wid	Hgt	Weight(Kg)	Cubic(m <sup>3</sup> )	EAN13	GTIN/DUN14
B1611BKR36	Black	68.0	55.0	38.0	1.5150	0.1421	8052530123065	
B1611BKR37	Black	68.0	55.0	38.0	1.7650	0.1421	8052530123072	
B1611BKR38	Black	68.0	55.0	38.0	1.7920	0.1421	8052530123089	
B1611BKR39	Black	78.0	36.0	40.0	1.8380	0.1123	8052530123096	
B1611BKR40	Black	78.0	36.0	40.0	1.9530	0.1123	8052530123102	
B1611BKR41	Black	78.0	36.0	40.0	2.0000	0.1123	8052530123119	
B1611BKR42	Black	78.0	36.0	40.0	2.0490	0.1123	8052530123126	
B1611BKR43	Black	78.0	36.0	40.0	2.1370	0.1123	8052530123133	
B1611BKR44	Black	78.0	36.0	40.0	2.2330	0.1123	8052530123140	
B1611BKR45	Black	78.0	36.0	40.0	2.2940	0.1123	8052530123157	
B1611BKR46	Black	78.0	36.0	40.0	2.3740	0.1123	8052530123164	
B1611BKR47	Black	78.0	36.0	40.0	2.4700	0.1123	8052530123171	
B1611BKR48	Black	78.0	36.0	40.0	2.4910	0.1123	8052530123188	