

B1704A - Berlin S1PS ESD LG SC FO SR

Collection: Run@Work

Upper: TECHNICAL FABRIC

Insole: Wire Lace System

Lining: Hi-tech 3D fabric

Midsole: TPU

Toecap: SlimCap

Sole: AirTech Anti-Fatigue + Tpu-Skin

Outer Carton: 10

Run@Work

Run@Work by Base Protection: A sporty and technologically advanced collection of work shoes designed for comfort and safety. Drawing inspiration from racing, its gritty style and vibrant colours ensure enhanced support and natural movement for workers.

Base

Comfort is what has inspired Base Protection since its first day of activity. The company produces safety footwear, combining technology and functional requirements, to respond to professional and more demanding clients.

Standards

EN ISO 20345:2022 S1PS (ESD LG SC FO SR)

**NO
IMAGE
AVAILABLE**

Features

- 200 joules resistant toe-cap
- Anti-static footwear
- Shock absorption in the heel region
- Puncture Resistant 3mm
- Protective scuff cap
- Ladder grips
- Suitable for use in ESD environments
- Metal free
- Women's Width 10.5
- Men's Width 12
- Vegan-friendly safety footwear

B1704A - Berlin S1PS ESD LG SC FO SR
Commodity Code: 6404199000

Test House

Cert No: N° F-113-07658-24

Carton Dimensions/Weight

Item	Colour	Len	Wid	Hgt	Weight(Kg)	Cubic(m ³)	EAN13	GTIN/DUN14
B1704ABKO35		68.0	41.0	38.0	1.0510	0.1059	8050503220001	
B1704ABKO36		68.0	41.0	38.0	1.0900	0.1059	8050503220018	
B1704ABKO37		68.0	41.0	38.0	1.1390	0.1059	8050503220025	
B1704ABKO38		68.0	41.0	38.0	1.1450	0.1059	8050503220032	
B1704ABKO39		68.0	41.0	38.0	1.2010	0.1059	8050503220049	
B1704ABKO40		68.0	41.0	38.0	1.2110	0.1059	8050503220056	
B1704ABKO41		68.0	41.0	38.0	1.2870	0.1059	8050503220063	
B1704ABKO42		68.0	41.0	38.0	1.3160	0.1059	8050503220070	
B1704ABKO43		68.0	41.0	38.0	1.3810	0.1059	8050503220087	
B1704ABKO44		68.0	41.0	38.0	1.4130	0.1059	8050503220094	
B1704ABKO45		68.0	41.0	38.0	1.5000	0.1059	8050503220100	
B1704ABKO46		68.0	41.0	38.0	1.4970	0.1059	8050503220117	
B1704ABKO47		68.0	41.0	38.0	1.6460	0.1059	8050503220124	
B1704ABKO48		68.0	41.0	38.0	1.6740	0.1059	8050503220131	