

B1711B - Amsterdam S3S ESD CI LG FO SR

Collection: Run@Work

Upper: Waxy Full-Grain Buffalo Leather

Insole: Wire Lace System

Lining: Hi-tech 3D fabric

Midsole: TPU

Toecap: SlimCap

Sole: AirTech Anti-Fatigue + Tpu-Skin

Outer Carton: 10

Run@Work

Run@Work by Base Protection: A sporty and technologically advanced collection of work shoes designed for comfort and safety. Drawing inspiration from racing, its gritty style and vibrant colours ensure enhanced support and natural movement for workers.

Base

Comfort is what has inspired Base Protection since its first day of activity. The company produces safety footwear, combining technology and functional requirements, to respond to professional and more demanding clients.

Standards

EN ISO 20345:2022 S3S (ESD CI LG FO SR)

**NO
IMAGE
AVAILABLE**

Features

- 200 joules resistant toe-cap
- Shock absorption in the heel region
- Anti-static footwear
- Water resistant
- Protective scuff cap
- Puncture Resistant 3mm
- Ladder grips
- Slip, fuel and oil resistant rubber outsole
- Metal free
- Women's Width 10.5
- Men's Width 12

B1711B - Amsterdam S3S ESD CI LG FO SR
Commodity Code: 6403993300

Test House

Cert No: N° F-113-07900-24

Carton Dimensions/Weight

Item	Colour	Len	Wid	Hgt	Weight(Kg)	Cubic(m ³)	EAN13	GTIN/DUN14
B1711BBKO35		68.0	41.0	38.0	1.0800	0.1059	8050503221121	
B1711BBKO36		68.0	41.0	38.0	1.1260	0.1059	8050503221138	
B1711BBKO37		68.0	41.0	38.0	1.1660	0.1059	8050503221145	
B1711BBKO38		68.0	41.0	38.0	1.1880	0.1059	8050503221152	
B1711BBKO39		68.0	41.0	38.0	1.2210	0.1059	8050503221169	
B1711BBKO40		68.0	41.0	38.0	1.2760	0.1059	8050503221176	
B1711BBKO41		68.0	41.0	38.0	1.3330	0.1059	8050503221183	
B1711BBKO42		68.0	41.0	38.0	1.3510	0.1059	8050503221190	
B1711BBKO43		68.0	41.0	38.0	1.4230	0.1059	8050503221206	
B1711BBKO44		68.0	41.0	38.0	1.4320	0.1059	8050503221213	
B1711BBKO45		68.0	41.0	38.0	1.5110	0.1059	8050503221220	
B1711BBKO46		68.0	41.0	38.0	1.5380	0.1059	8050503221237	
B1711BBKO47		68.0	41.0	38.0	1.6650	0.1059	8050503221244	
B1711BBKO48		68.0	41.0	38.0	1.7010	0.1059	8050503221251	