

### C470 - Hi-Vis Band and Brace Vest

**Collection:** Vest-Port

**Range:** High Visibility

**Shell Fabric:** 100% Polyester, Warp Knit 124g

#### Product information

The best selling C470 with classic reflective tape configuration will ensure you are seen. Available in all three EN ISO 20471 conforming colours.

#### Standards

EN ISO 20471 Class 2  
RIS 3279 TOM Issue 2 (Orange Only)  
ANSI/ISEA 107 TYPE R CLASS 2  
ANSI/ISEA 107 TYPE P CLASS 2  
AS/NZS 4602.1 Class D/N  
AS/NZS 1906.4

#### Vest-Port

The Vest-Port™ extensive range of vests covers the varied demands of the work environment from core styles to the revolutionary "Executive" design, which is now available in both summer and winter weights.

#### High Visibility

Our extensive range of High-Visibility clothing meets stringent requirements in both design and construction, to ensure compliance with the latest EN ISO 20471 & ANSI standards. Innovative and technical, our High Visibility range is ideal for those who will not compromise on style, comfort, protection and performance.

#### Features

- Lightweight and comfortable
- Reflective tape for increased visibility
- Hook and loop closure for easy access
- Generous fit for wearer comfort
- Certified to EN ISO 20471 after 50x washes
- Complies with RIS 3279-TOM for rail industry (orange only)



Orange S/M-6XL/7XL,  
Yellow S/M-6XL/7XL,  
Red S/M-XXL/3XL

### C470 - Hi-Vis Band and Brace Vest Commodity Code: 6110309100

#### Test House

SATRA Technology Europe Ltd (Notified Body No.: NB: 2777)  
Bracetown Business Park  
D15 YN2P, Ireland  
Cert No: 2777/13422-02/E00-00

SATRA Technology Centre Ltd (Notified Body No.: AB: 0321)  
SATRA Technology Park  
NN16 8SD, United Kingdom  
Cert No: AB0321/16796-01/E00-00

#### Wash Care



#### Carton Dimensions/Weight

Item	Colour	Len	Wid	Hgt	Weight(Kg)	Cubic(m <sup>3</sup> )	EAN13	GTIN/DUN14
C470RERS/M	Red	43.0	28.0	55.0	0.1560	0.0662	5036108169146	25036108613292
C470RERL/XL	Red	43.0	28.0	55.0	0.1700	0.0662	5036108169139	25036108613285
C470RERXX/3X	Red	45.0	28.0	55.0	0.1780	0.0693	5036108169153	25036108613308