

FF50 - Aberdeen FR Coverall

Collection: Bizflame™ Work

Range: Flame Resistant Multi-Norm

Shell Fabric: Bizflame Work: 99% Cotton, 1% Carbon Fibre 350g

Product information

Ideally suited to off shore industries this top of the range coverall comes in inch sizes for the perfect fit. Certified to a multitude of international standards the Aberdeen coverall offers top protection in a range of hazardous environments.

Standards

EN ISO 11612 (A1+A2, B1, C1, E2, F1)

EN ISO 11611 Class 2 (A1+A2)

EN 1149 -5

IEC 61482-2 IEC 61482-1-1 (ELIM 8.6 CAL/CM², ATPV 9.8 CAL/CM²)

IEC 61482-2 IEC 61482-1-2 APC 1

ASTM F1959/F1959M-12 (ATPV=13.6 Cal/CM² (HAF=82%))

Bizflame™ Work

BizFlame™ Work has been developed and designed using a highly innovative flame resistant fabric with added anti-static properties. Constructed from 99% cotton and interwoven with 1% carbon fibres. Excellent tear and tensile strength offer durability while the premium quality cotton fibres give the fabric unrivalled comfort. Inherent anti-static carbon fibre

Flame Resistant Multi-Norm

This industry leading flame resistant range provides multi-standard protection for hazardous environments. These state of the art products are the result of years of experience combined with advanced technology and market research. Commitment to the health, safety and comfort of the wearer can be seen in the wide range of products suitable for all climates and end uses.

Features

- Protection against radiant, convective and contact heat
- Class 2 welding protection
- Two back patch pockets
- Rule pocket
- Stud adjustable cuffs for a secure fit
- Triple-stitched seams for extra durability



FF50 - Aberdeen FR Coverall
Commodity Code: 6211321000

Test House

SATRA Technology Europe Ltd (Notified Body No.: NB: 2777)
 Bracetown Business Park
 D15 YN2P, Ireland
 Cert No: 2777/13136-03/E00-00

Wash Care



Carton Dimensions/Weight

| Item | Colour | Len | Wid | Hgt | Weight(Kg) | Cubic(m ³) | EAN13 | GTIN/DUN14 |
|-----------|--------|------|------|------|------------|------------------------|---------------|----------------|
| FF50ORR36 | Orange | 43.0 | 28.0 | 50.0 | 1.5400 | 0.0602 | 5036108258598 | 25036108747782 |
| FF50ORR38 | Orange | 43.0 | 28.0 | 50.0 | 1.5400 | 0.0602 | 5036108258604 | 25036108747799 |
| FF50ORR40 | Orange | 43.0 | 28.0 | 50.0 | 1.5900 | 0.0602 | 5036108258611 | 25036108747805 |
| FF50ORR41 | Orange | 43.0 | 28.0 | 50.0 | 1.6500 | 0.0602 | 5036108275687 | 25036108765779 |
| FF50ORR42 | Orange | 43.0 | 28.0 | 50.0 | 1.6200 | 0.0602 | 5036108258628 | 25036108747812 |
| FF50ORR44 | Orange | 43.0 | 28.0 | 50.0 | 1.6900 | 0.0602 | 5036108258635 | 25036108747829 |
| FF50ORR46 | Orange | 43.0 | 28.0 | 50.0 | 1.7300 | 0.0602 | 5036108258642 | 25036108747836 |
| FF50ORR47 | Orange | 43.0 | 28.0 | 50.0 | 1.7400 | 0.0602 | 5036108275694 | 25036108765786 |
| FF50ORR48 | Orange | 43.0 | 28.0 | 50.0 | 1.7400 | 0.0602 | 5036108258659 | 25036108747843 |
| FF50ORR50 | Orange | 43.0 | 28.0 | 50.0 | 1.7900 | 0.0602 | 5036108258666 | 25036108747850 |
| FF50ORR52 | Orange | 43.0 | 28.0 | 50.0 | 1.7900 | 0.0602 | 5036108258673 | 25036108747867 |
| FF50ORR54 | Orange | 43.0 | 28.0 | 50.0 | 1.8800 | 0.0602 | 5036108258680 | 25036108747874 |