

PRODUCT SPECIFICATION & TECHNICAL DATASHEET

FR10 - Modaflame Knit FR Long Sleeve Polo Shirt

Collection: Modaflame™ Knit **Range:** Flame Resistant Multi-Norm **Shell Fabric:** Modaflame Knit: 60% Modacrylic, 39% Cotton, 1% Carbon Fibre 200g

Product information

Convenient for cooler weather and ideal for workers in industries exposed to heat. The stylish design of the garment has a 3-button placket, finished with a ribbed collar and cuffs.

Standards

EN ISO 11612 (A1, B1, C1, F1) EN 1149 -5 IEC 61482-2 IEC 61482-1-1 (ELIM 4.4 CAL/CM², EBT 5.5 CAL/CM²) IEC 61482-2 IEC 61482-1-2 APC 1 ASTM F1959/F1959M-12 (EBT = 4.3 CAL/CM² (HAF = 66%))

Modaflame[™] Knit

Constructed from an inherently fire resistant yarn of 60% Modacrylic, 39% Cotton and 1% Carbon Fibre. Tested to meet and adhere to the required EN Standards, Modaflame[™] Knit is strong, durable and highly innovative.

Flame Resistant Multi-Norm

This industry leading flame resistant range provides multi-standard protection for hazardous environments. These state of the art products are the result of years of experience combined with advanced technology and market research. Commitment to the health, safety and comfort of the wearer can be seen in the wide range of products suitable for all climates and end uses.

Features

- Inherent flame resistant qualities will not diminish with washing
- Protection against radiant, convective and contact heat
- High cotton content for superior comfort
- Button placket opening
- Ribbed cuffs for added comfort
- Ribbed collar





FR10 - Modaflame Knit FR Long Sleeve Polo Shirt Commodity Code: 6105201000

Test House

SATRA Technology Europe Ltd (Notified Body No.: NB: 2777) Bracetown Business Park D15 YN2P, Ireland Cert No: 2777/13282-05/E00-00



Carton Dimensions/Weight

Colour	Len	Wid	Hgt	Weight(Kg)	Cubic(m ³)	EAN13	GTIN/DUN14
Black	55.0	36.0	42.0	0.3600	0.0832	5036108224241	25036108711585
Black	55.0	36.0	42.0	0.3800	0.0832	5036108224234	25036108711578
Black	55.0	36.0	42.0	0.4280	0.0832	5036108224227	25036108711561
Black	55.0	36.0	42.0	0.4200	0.0832	5036108224258	25036108711592
Black	55.0	36.0	50.0	0.4400	0.0990	5036108224265	25036108711608
Black	55.0	36.0	50.0	0.4600	0.0990	5036108224272	25036108711615
Black	55.0	36.0	50.0	0.4800	0.0990	5036108381364	25036108865981
	Black Black Black Black Black Black	Black55.0Black55.0Black55.0Black55.0Black55.0Black55.0Black55.0	Black 55.0 36.0 Black 55.0 36.0	Black 55.0 36.0 42.0 Black 55.0 36.0 50.0 Black 55.0 36.0 50.0 Black 55.0 36.0 50.0	Black 55.0 36.0 42.0 0.3600 Black 55.0 36.0 42.0 0.3800 Black 55.0 36.0 42.0 0.4280 Black 55.0 36.0 42.0 0.4200 Black 55.0 36.0 50.0 0.4400 Black 55.0 36.0 50.0 0.4600	Black 55.0 36.0 42.0 0.3600 0.0832 Black 55.0 36.0 42.0 0.3800 0.0832 Black 55.0 36.0 42.0 0.4280 0.0832 Black 55.0 36.0 42.0 0.4280 0.0832 Black 55.0 36.0 42.0 0.4200 0.0832 Black 55.0 36.0 50.0 0.4400 0.0990 Black 55.0 36.0 50.0 0.4600 0.0990	Black55.036.042.00.36000.08325036108224241Black55.036.042.00.38000.08325036108224234Black55.036.042.00.42800.08325036108224227Black55.036.042.00.42000.08325036108224258Black55.036.050.00.44000.09905036108224265Black55.036.050.00.44000.09905036108224272