

FT13 - Steelite Rigger Boot Pro S3 CI

Collection: Steelite™ Work

Range: Foot Protection

Material Upper: Action Leather

Material Outsole: PU/PU

Product information

Total comfort, fur lined rigger boot. The steel toecap and penetration resistant midsole keep your feet safe while the modern upper design ensures robust, reliable protection with reinforced ankle protection, scuff cap and heel kick. Fur lined for increased insulation in cold environments.

Standards

EN ISO 20345: 2011 S3



Steelite™ Work

Fully Compliant with all current standards, ideal for industrial wear with a strong and flexible construction.

Foot Protection

Innovation, design, styling and quality components define the Portwest foot protection collection.

Features

- Fur lined for added warmth and comfort
- Protective TPU scuff cap for high impact
- Reinforced ankle protection
- Kick spur
- Side pull-tabs
- Cold insulation
- CE certified
- UKCA marked
- Protective steel toecap
- Pierce resistant steel midsole
- Anti-static footwear



FT13 - Steelite Rigger Boot Pro S3 CI
Commodity Code: 6403400000

Test House

Intertek Italia S.p.A. (Notified Body No.: NB: 2575)

Via Guido Miglioli 2/A,

-, Italy

Cert No: ITASLNB22003502

Carton Dimensions/Weight

Item	Colour	Len	Wid	Hgt	Weight(Kg)	Cubic(m ³)	EAN13	GTIN/DUN14
FT13TAR38	Tan	70.0	64.0	35.0	1.6270	0.1568	5036108274895	25036108764970
FT13TAR39	Tan	70.0	64.0	35.0	1.6800	0.1568	5036108274901	25036108764987
FT13TAR40	Tan	70.0	64.0	35.0	1.6900	0.1568	5036108274918	25036108764994
FT13TAR41	Tan	70.0	64.0	35.0	1.7240	0.1568	5036108274925	25036108765007
FT13TAR42	Tan	70.0	64.0	35.0	1.7540	0.1568	5036108274932	25036108765014
FT13TAR43	Tan	70.0	64.0	35.0	1.7980	0.1568	5036108274949	25036108765021
FT13TAR44	Tan	72.0	64.0	37.0	1.8980	0.1705	5036108274956	25036108765038
FT13TAR45	Tan	72.0	64.0	37.0	1.9540	0.1705	5036108274963	25036108765045
FT13TAR46	Tan	72.0	64.0	37.0	2.1320	0.1705	5036108274970	25036108765052
FT13TAR47	Tan	72.0	64.0	37.0	2.1870	0.1705	5036108274987	25036108765069
FT13TAR48	Tan	72.0	64.0	37.0	2.2360	0.1705	5036108274994	25036108765076