

### SK20 - Modaflame Knit FR Sock

**Collection:** Modaflame™

**Range:** Flame Resistant Multi-Norm

**Inner Pack:** 6

**Outer Carton:** 144

#### Product information

Our Modaflame Sock offers the wearer great protection and comfort. The leg of the sock is elasticated for a snug fit.

#### Modaflame™

Garments can be layered to achieve an overall Arc Thermal Performance Value (ATPV) or Energy Break open threshold (Ebt) Rating. For example, thermals may achieve an Ebt of 4.3 cal/cm2, and an outer coverall may achieve an ATPV of 13.6cal/cm2. However the combination ATPV will be greater than the sum of the two single layers, as the air gap between the two layers affords the wearer additional protection.

#### Flame Resistant Multi-Norm

This industry leading flame resistant range provides multi-standard protection for hazardous environments. These state of the art products are the result of years of experience combined with advanced technology and market research. Commitment to the health, safety and comfort of the wearer can be seen in the wide range of products suitable for all climates and end uses.

#### Standards

EN ISO 14116

EN 1149 -3



#### Features

- Sock height 28cm
- Inherent flame resistant qualities will not diminish with washing
- Elasticated for a comfortable fit
- Knit gauge 12 for shape retention
- Seamless toe sock providing a snug and secure fit
- Two tone design
- Anti-static
- Retail tag which aids presentation for retail sales
- CE certified



## PRODUCT SPECIFICATION & TECHNICAL DATASHEET

### SK20 - Modaflake Knit FR Sock

**Commodity Code: 6115969900**

#### Test House

SATRA Technology Europe Ltd (Notified Body No.: NB: 2777)

Bracetown Business Park

D15 YN2P, Ireland

Cert No: 2777/25198-01/E00-00

#### Wash Care



#### Carton Dimensions/Weight

Item	Colour	Len	Wid	Hgt	Weight(Kg)	Cubic(m <sup>3</sup> )	EAN13	GTIN/DUN14
SK20BKR39-43	Black	65.0	45.0	47.0	0.0580	0.1375	5036108174348	15036108668516
SK20BKR44-48	Black	65.0	45.0	47.0	0.0740	0.1375	5036108174355	15036108668523