

## A450 - Weatherproof Hi-Vis Glove

**Collection:** Thermal Protection Gloves

**Range:** Hand Protection

**Materials:** Cotton, Polyurethane

**Dipping:**

**Inner Pack:** 6

**Outer Carton:** 96

### Product information

The A450 is designed for use in the most demanding conditions. By having an insulated liner and knitwrist the user keeps their hands warm and dry. A tough double dipped PVC coating prevents oil, grease and water penetration.

### Thermal Protection Gloves

When cold thermal hazards are present, the hands' motor skills can be greatly reduced, this leads to increased risk of accidents and injury. Specially designed thermal protective gloves are available to combat these dangers in hazardous environments.

### Hand Protection

A wide and increasing range of hand protection products is available. In order to help cater to every need. Only the best materials and manufacturing methods are used in the production of Portwests' extensive range of Hand Protection products....

### Standards

EN ISO 21420: 2020

EN 388: 2016 + A1: 2018 (3121X)

EN 511: 2006 (11X)



### Features

- Fully coated for maximum liquid protection
- Double dipped coating for durability
- Prevents grease, oil and water penetration
- 12 gauge liner for dexterity
- Knitted cuff for comfort and warmth
- Suitable for any work area where oil and grease resistance is a priority
- CE certified

**A450 - Weatherproof Hi-Vis Glove**  
**Commodity Code: 6116108091**

**Test House**  
SATRA Technology Europe Ltd    (Notified Body No.: NB: 2777)  
Bracetown Business Park  
D15 YN2P, Ireland  
Cert No: 2777/21356-01/E00-00

SATRA Technology Centre Ltd    (Notified Body No.: AB: 0321)  
SATRA Technology Park  
NN16 8SD, United Kingdom  
Cert No: AB0321/21640-01/E00-00

**Carton Dimensions/Weight**

| Item      | Colour | Len  | Wid  | Hgt  | Weight(Kg) | Cubic(m³) | EAN13         | GTIN/DUN14     |
|-----------|--------|------|------|------|------------|-----------|---------------|----------------|
| A450ORRXL | Orange | 56.0 | 30.0 | 48.0 | 0.2120     | 0.0806    | 5036108211883 | 25036108690088 |