

B0667 - Grand Canyon Mid

Collection: Record

Upper: Microfibre + Hi-Tech Fabric

Insole: Wire Lace System

Lining: SmellStop Antibacterial

Midsole: Fresh'n Flex

Toecap: SlimCap

Sole: AirTech + Tpu-Skin

Outer Carton: 10

Record

Record antifatigue footwear collection offers an answer to the demand for lightweight design.

Base

Comfort is what has inspired Base Protection since its first day of activity. The company produces safety footwear, combining technology and functional requirements, to respond to professional and more demanding clients.



Standards

EN ISO 20345:2022 S1P (FO ESD SR)
CEI EN 61340-4-3 S1P

Features

- 200 joules resistant toe-cap
- Puncture resistant sole
- Shock absorption in the heel region
- Anti-static footwear
- Hydrocarbons resistant
- Electronic devices protection from electrostatic discharges
- Metal free
- Orthopaedic made to measure footbed, complying with european norms DGUV112-191
- Women's width
- Men's width
- SRC - Slip resistant outsole to prevent slips and trips on ceramic and steel surfaces

B0667 - Grand Canyon Mid
Commodity Code: 6404199000

Test House
Cert No: N° F-113-05778-22

Carton Dimensions/Weight

Item	Colour	Len	Wid	Hgt	Weight(Kg)	Cubic(m³)	EAN13	GTIN/DUN14
B0667BKR35	Black	68.0	41.0	38.0	1.0280	0.1059	8052530126790	
B0667BKR36	Black	68.0	41.0	38.0	1.0920	0.1059	8052530126509	
B0667BKR37	Black	68.0	41.0	38.0	1.1160	0.1059	8052530126516	
B0667BKR38	Black	68.0	41.0	38.0	1.1270	0.1059	8052530126523	
B0667BKR39	Black	68.0	41.0	38.0	1.2110	0.1059	8052530126530	
B0667BKR40	Black	68.0	41.0	38.0	1.2170	0.1059	8052530126547	
B0667BKR41	Black	68.0	55.0	38.0	1.2860	0.1421	8052530126554	
B0667BKR42	Black	68.0	55.0	38.0	1.3630	0.1421	8052530126561	
B0667BKR43	Black	68.0	55.0	38.0	1.4180	0.1421	8052530126578	
B0667BKR44	Black	68.0	55.0	38.0	1.3860	0.1421	8052530126585	
B0667BKR45	Black	68.0	55.0	38.0	1.4780	0.1421	8052530126592	
B0667BKR46	Black	68.0	55.0	38.0	1.5050	0.1421	8052530126608	
B0667BKR47	Black	68.0	55.0	38.0	1.5990	0.1421	8052530126615	
B0667BKR48	Black	68.0	55.0	38.0	1.6330	0.1421	8052530126622	