

B1219 - I-WIRE S3 ESD SRC

Collection: I4

Upper: Water Resistant Technical Textile

Insole: Wire Lace System

Lining: SmellStop Antibacterial

Midsole: Fresh'n Flex

Toecap: SlimCap

Sole: AirTech + Tpu-Skin

Outer Carton: 10

I4

Inspired by the world of industry 4.0, the new i4 line combines maximum stability in the back part and high flexibility in the front. i4 guarantees comfort, balance and safety for those who spend a lot of time standing and for those who make repeated flexions and movements.



Standards

EN ISO 20345: 2011 S3 (ESD SRC)

EN 61340-4-3 Class 3

Features

- Anti-static footwear
- Shock absorption in the heel region
- Puncture resistant sole
- 200 joules resistant toe-cap
- Water resistant upper
- Hydrocarbons resistant
- Metal free
- Electronic devices protection from electrostatic discharges
- Men's width
- Women's width
- BOA® closing system

B1219 - I-WIRE S3 ESD SRC
Commodity Code: 6403993300

Test House
A.N.C.I. Servizi S.R.L (CIMAC) (Notified Body No.: NB: 0465)
Via Alberto Riva Villasanta, 3
, Italy
Cert No: F-113-05308-22

Carton Dimensions/Weight

Item	Colour	Len	Wid	Hgt	Weight(Kg)	Cubic(m³)	EAN13	GTIN/DUN14
B1219BKB35	Black/Blue	68.0	41.0	38.0	1.0560	0.1059	8052530121504	
B1219BKB36	Black/Blue	68.0	41.0	38.0	1.0960	0.1059	8052530121511	
B1219BKB37	Black/Blue	68.0	41.0	38.0	1.1440	0.1059	8052530121528	
B1219BKB38	Black/Blue	68.0	41.0	38.0	1.1800	0.1059	8052530121535	
B1219BKB39	Black/Blue	68.0	41.0	38.0	1.2200	0.1059	8052530121542	
B1219BKB40	Black/Blue	68.0	41.0	38.0	1.2770	0.1059	8052530121559	
B1219BKB41	Black/Blue	68.0	41.0	38.0	1.3280	0.1059	8052530121566	
B1219BKB42	Black/Blue	68.0	41.0	38.0	1.3660	0.1059	8052530121573	
B1219BKB43	Black/Blue	68.0	41.0	38.0	1.4380	0.1059	8052530121580	
B1219BKB44	Black/Blue	68.0	41.0	38.0	1.4840	0.1059	8052530121597	
B1219BKB45	Black/Blue	68.0	41.0	38.0	1.5160	0.1059	8052530121603	
B1219BKB46	Black/Blue	68.0	41.0	38.0	1.5920	0.1059	8052530121610	
B1219BKB47	Black/Blue	68.0	41.0	38.0	1.6550	0.1059	8052530121627	
B1219BKB48	Black/Blue	68.0	41.0	38.0	1.7090	0.1059	8052530121634	