

FR64 - FR Molten Metal Trousers

Collection: Aluflame™

Range: Flame Resistant

Shell Fabric: Aluflame Work: 43% Cotton, 30% Viscose, 20% Acrylic, 6% Para Aramid, 1% Carbon Fibre

Outer Carton: 18

Product information

Developed for the demanding environment of aluminium, iron and steel works, this inherent fabric offers maximum protection.

Aluflame™

Aluflame

Flame Resistant

This industry leading flame resistant range provides multi standard protection for hazardous environments. These state of the art products are the result of years of experience combined with advanced technology and market research. Commitment to the health, safety and comfort of the wearer can be seen in the wide range of products suitable for all climates and end uses.

Standards

EN ISO 11612 (A1+A2, B1, C1, D3, E3, F1)

EN ISO 11611 Class 2 (A1+A2)

EN 1149 -5

IEC 61482-2 IEC 61482-1-1 (ELIM 8.1 CAL/CM²)

IEC 61482-2 IEC 61482-1-2 APC 1

ASTM F1959/F1959M-14e1 (ATPV=13 Cal/CM² (HAF=84.9%))



Features

- Highest protection against molten aluminium
- Class 2 welding protection
- Certified protection against molten metal splash
- Rule pocket
- Jetted back pocket
- Half elasticated waist for a secure and comfortable fit
- 4 pockets for ample storage
- CE certified
- New style
- 40+ UPF rated fabric to block 98% of UV rays
- CE-CAT III

PORTWEST®



FR64 - FR Molten Metal Trousers
Commodity Code: 6203491100

Test House
SATRA Technology Centre Ltd (Notified Body No.: AB: 0321)
SATRA Technology Park
NN16 8SD, United Kingdom
Cert No: 2777/25491-01/E00-00

Wash Care



Carton Dimensions/Weight

Item	Colour	Len	Wid	Hgt	Weight(Kg)	Cubic(m³)	EAN13	GTIN/DUN14
FR64NARS	Navy	65.0	40.0	20.0	0.7650	0.0520	5036108351992	15036108840615
FR64NARM	Navy	65.0	40.0	20.0	0.8050	0.0520	5036108351985	15036108840608
FR64NARL	Navy	65.0	40.0	20.0	0.8390	0.0520	5036108351978	15036108840592
FR64NARXL	Navy	65.0	40.0	20.0	0.8780	0.0520	5036108352005	15036108840622
FR64NARXXL	Navy	65.0	40.0	23.0	0.9210	0.0598	5036108352012	15036108840639
FR64NARXXXL	Navy	65.0	40.0	23.0	0.9570	0.0598	5036108352029	15036108840646