

### FR65 - FR Molten Metal Jacket

**Collection:** Aluflame™

**Range:** Flame Resistant

**Shell Fabric:** Aluflame Work: 43% Cotton, 30% Viscose, 20% Acrylic, 6% Para Aramid, 1% Carbon Fibre

**Outer Carton:** 18

#### Product information

Developed for the demanding environment of aluminium, iron and steel works, the inherent lightweight fabric offers maximum protection.

**Aluflame™**

Aluflame

#### Flame Resistant

This industry leading flame resistant range provides multi standard protection for hazardous environments. These state of the art products are the result of years of experience combined with advanced technology and market research. Commitment to the health, safety and comfort of the wearer can be seen in the wide range of products suitable for all climates and end uses.

#### Standards

EN ISO 11612 (A1+A2, B1, C1, D3, E3, F1)

EN ISO 11611 Class 2 (A1+A2)

EN 1149 -5

IEC 61482-2 IEC 61482-1-1 (ELIM 8.1 CAL/CM<sup>2</sup>)

IEC 61482-2 IEC 61482-1-2 APC 1

ASTM F1959/F1959M-14e1 (ATPV=13 Cal/CM<sup>2</sup> (HAF=84.9%))



#### Features

- Highest protection against molten aluminium
- Class 2 welding protection
- Certified protection against molten metal splash
- Stud adjustable cuffs for a secure fit
- Radio loops for easy clipping of a radio
- 2 pockets for secure storage
- CE certified
- New style
- 40+ UPF rated fabric to block 98% of UV rays
- CE-CAT III
- UKCA marked



PRODUCT SPECIFICATION & TECHNICAL DATASHEET

FR65 - FR Molten Metal Jacket  
Commodity Code: 6203391100

**Test House**  
SATRA Technology Europe Ltd (Notified Body No.: NB: 2777)  
Bracetown Business Park  
D15 YN2P, Ireland  
Cert No: 2777/25491-01/E00-00

Wash Care



Carton Dimensions/Weight

| Item        | Colour | Len  | Wid  | Hgt  | Weight(Kg) | Cubic(m³) | EAN13         | GTIN/DUN14     |
|-------------|--------|------|------|------|------------|-----------|---------------|----------------|
| FR65NARS    | Navy   | 65.0 | 40.0 | 26.0 | 0.9290     | 0.0676    | 5036108352050 | 15036108840677 |
| FR65NARM    | Navy   | 65.0 | 40.0 | 26.0 | 0.9600     | 0.0676    | 5036108352043 | 15036108840660 |
| FR65NARL    | Navy   | 65.0 | 40.0 | 26.0 | 1.0020     | 0.0676    | 5036108352036 | 15036108840653 |
| FR65NARXL   | Navy   | 65.0 | 40.0 | 26.0 | 1.0580     | 0.0676    | 5036108352067 | 15036108840684 |
| FR65NARXXL  | Navy   | 65.0 | 40.0 | 26.0 | 1.0900     | 0.0676    | 5036108352074 | 15036108840691 |
| FR65NARXXXL | Navy   | 65.0 | 40.0 | 26.0 | 1.1300     | 0.0676    | 5036108352081 | 15036108840707 |