# **PORTWEST**®



## **PS38 - Ultra Spectacles**

**Collection:** Eye Protection

Range: PPE

Materials: Polycarbonate, Nylon

Inner Pack: 12 Outer Carton: 144



Stylish wrap around spectacles with inclinable side arms, moulded nose bridge and a PC browguard for extra protection from glare or particles. Ultra spectacles are ideal for longer use thanks to extremely light weight and flexible temples. Safe for working on electrical applications as free from metal.



PORTWEST® eye protection range includes spectacles, safety goggles and visors, designed to protect the eyes and face of workers from injuries which may occur during working activities. TECHNICAL SPECTACLES: High performance and cutting edge styles. SPORT SPECTACLES: Light weight and modern design. CLASSIC SPECTACLES: Essential PPE safety eyewear styles.

#### PPE

Portwest Head PPE range applies the latest standards to deliver the highest level of protection. Comfortable and lightweight, the PPE range will ensure a pleasant wear, even for long periods of use. Your safety is our mission.

#### **Standards**

EN 166 (1 F) EN 170 (2C-1.2 (clear)) EN 170 (2-1.2 (amber)) EN 172 (5-3.1 (smoke)) ANSI/ISEA Z87 +



#### **Features**

- · Lightweight wrap-around design
- $\bullet \ \ Moulded \ browguard \ protection$
- Inclinable side arms for optimum fit
- Flexible arms for ultra comfort
- 100% metal free
- 99% UV protection
- Anti-scratch coating for added durability
- CE certified
- UKCA marked
- Retail bag which aids presentation for retail sales
- Individually packed for vending machines

# **PORTWEST**



**PS38 - Ultra Spectacles** 

**Commodity Code: 9004901000** 

**Test House** 

SGS FIMKO Ltd (Notified Body No.: NB: 0598)

Takomotie 8 , Finland

Contact: sgs.fimko@sgs.com Cert No: 0598/PPE/23/3140

SGS United Kingdom Limited (Notified Body No.: AB: 0120)

Rossmore Business Park

CH65 3EN, UK

Cert No: 0120/PPE/230525

### **Carton Dimensions/Weight**

Item	Colour	Len	Wid	Hgt	Weight(Kg)	Cubic(m³)	EAN13	GTIN/DUN14
PS38AMR	Amber	60.0	35.0	36.0	0.0230	0.0756	5036108420766	15036108906656