

PRODUCT SPECIFICATION & TECHNICAL DATASHEET

PV50 - Peak View Hard Hat Vented

Collection: Head Protection

Range: PPE

Materials: Polycarbonate, PE

Outer Carton: 20

Product information

Portwest exclusive design and Patented Model with innovative translucent shell to see through peak and sides: allows the wearer to look upwards without the need to tilt the head. Its extra strong yet ultra lightweight Polycarbonate shell offers protection from UV rays. Peak View features a 6-point textile harness with slip ratchet for size adjustment. Vented shell for extra air-flow.



Portwest's head protection range aims to benefit our customers by combining the most up to date styles and standards in head protection, irrespective of job or location. Innovative, comfortable and lightweight helmets available for multiple uses.

PPE

Portwest Head PPE range applies the latest standards to deliver the highest level of protection. Comfortable and lightweight, the PPE range will ensure a pleasant wear, even for long periods of use. Your safety is our mission.

Standards

EN 397 (-30°C/+50°C) ANSI/ISEA Z89.1 TYPE II (Class C)



Features

- Portwest exclusive design and patented model
- Translucent shell to see through peak and sides
- UV 400 stabilised
- Vented helmet shell to allow air circulation cooling the wearer's head
- 6-point textile suspension harness for enhanced wearer comfort and safety
- \bullet Size adjustable headband via slip ratchet system
- Extra strong yet ultra light weight Polycarbonate shell
- \bullet Soft foam sweat band included
- Compatible accessories available
- \bullet Available in multiple colourways
- Up to 7 years lifetime from manufacturing date (as long as undamaged)



PRODUCT SPECIFICATION & TECHNICAL DATASHEET

PV50 - Peak View Hard Hat Vented Commodity Code: 6506101000

Test House

BSI Group The Netherlands B.V. (Notified Body No.: NB: 2797)

John M. Keynesplein 9 , The Netherlands Cert No: CE 722820

Carton Dimensions/Weight

Item	Colour	Len	Wid	Hgt	Weight(Kg)	Cubic(m³)	EAN13	GTIN/DUN14
PV50CLR	Clear	59.0	38.0	47.0	0.4100	0.1054	5036108266371	15036108756046