

PRODUCT SPECIFICATION & TECHNICAL DATASHEET

TK40 - Oregon Softshell Jacket (2L)

Collection: Rainwear Softshell **Range:** All Weather Protection

Shell Fabric: 94% Polyester, 6% Elastane bonded to 100%

Polyester Micro Fleece (2L)

Outer Carton: 24

Product information

Clever styling and fabric is the foundation for this contemporary softshell. The jacket comprises two side pockets, a zipped mobile phone pocket to the chest and adjustable cuffs for a snug fit.

Rainwear Softshell

Technical and innovative, the TK2 softshell uses comfortable stretch woven fabrics and tight layered weaves to offer advanced water resistant, windproof and breathable properties. The sophistication of TK2 provides a water resistant garment of unequaled strength and comfort, while at the same time retaining exceptional suppleness.

All Weather Protection

Portwest All Weather Protection is engineered with exceptional fabrics and designs, allowing an easy transition between work and leisure. Tested to withstand the rigors of everyday wear, each garment has been designed and manufactured using the best quality materials and high technology construction techniques to ensure total satisfaction with wear after wear.

Standards

Waterproof / Breathability (WP 3,000mm, MVP 6,000g/m2/24hr)



Features

- · Cell phone
- 50+ UPF rated fabric to block 98% of UV rays
- · Hook and loop cuffs for a secure fit
- Available in sizes up to 4XL
- 2 layer
- 5 pockets for ample storage
- Durable, breathable, windproof and water resistant fabric
- Micro polar fleece lined and bonded with shell
- Extremely water resistant fabric finish, water beads away from fabric surface
- Water resistant zippers to prevent water penetration
- Drawcord adjustable hem



PRODUCT SPECIFICATION & TECHNICAL DATASHEET

TK40 - Oregon Softshell Jacket (2L) Commodity Code: 6101309000

Test House

Wash care



Carton Dimensions/Weight

Colour	Len	Wid	Hgt	Weight(Kg)	Cubic(m³)	EAN13	GTIN/DUN14
Navy	65.0	45.0	40.0	0.7840	0.1170	5036108168460	25036108669152
Navy	65.0	45.0	40.0	0.7520	0.1170	5036108168453	25036108669145
Navy	65.0	45.0	40.0	0.8460	0.1170	5036108168446	25036108669138
Navy	65.0	45.0	40.0	0.8600	0.1170	5036108168477	25036108669169
Navy	65.0	45.0	40.0	0.8800	0.1170	5036108168484	25036108669176
Navy	65.0	45.0	40.0	0.8940	0.1170	5036108168491	25036108773743
Navy	65.0	45.0	40.0	0.9480	0.1170	5036108210602	
	Navy Navy Navy Navy Navy	Navy 65.0 Navy 65.0 Navy 65.0 Navy 65.0 Navy 65.0 Navy 65.0	Navy 65.0 45.0 Navy 65.0 45.0	Navy 65.0 45.0 40.0	Navy 65.0 45.0 40.0 0.7840 Navy 65.0 45.0 40.0 0.7520 Navy 65.0 45.0 40.0 0.8460 Navy 65.0 45.0 40.0 0.8600 Navy 65.0 45.0 40.0 0.8800 Navy 65.0 45.0 40.0 0.8940	Navy 65.0 45.0 40.0 0.7840 0.1170 Navy 65.0 45.0 40.0 0.7520 0.1170 Navy 65.0 45.0 40.0 0.8460 0.1170 Navy 65.0 45.0 40.0 0.8600 0.1170 Navy 65.0 45.0 40.0 0.8800 0.1170 Navy 65.0 45.0 40.0 0.8940 0.1170 Navy 65.0 45.0 40.0 0.8940 0.1170	Navy 65.0 45.0 40.0 0.7840 0.1170 5036108168460 Navy 65.0 45.0 40.0 0.7520 0.1170 5036108168453 Navy 65.0 45.0 40.0 0.8460 0.1170 5036108168446 Navy 65.0 45.0 40.0 0.8600 0.1170 5036108168477 Navy 65.0 45.0 40.0 0.8800 0.1170 5036108168484 Navy 65.0 45.0 40.0 0.8940 0.1170 5036108168491